

Dupont™ Plantex® Pro Installation guide

Step 1: Preparation

Prepare the ground and rake if necessary. Ensure that the ground is free of rubble, sharp stones and weeds before laying Plantex® Pro to prevent damage to the fabric.

Step 2: Roll out

Roll out Plantex® Pro. If several rolls are laid side by side, ensure there is an overlap of at least 10 cm.

Step 3: Secure

Apply at least 2 pins per running. On large unplanted areas weigh down Plantex® Pro with stones or with the new plants to ensure that no movement occurs whilst planting through.

Step 4: Cut

Using sharp scissors or a knife, make an "X-shaped" cut above an existing plant or in the spot where the new plant is to be placed.

Step 5: Plant

Work Plantex® Pro gently over existing plants or plant through with new ones.

Step 6: Cover

Plantex® Pro must be covered with at least a 5 cm layer of mulch e.g. bark, straw, gravel, decorative chippings etc. The top cover should be thick enough to fully cover the fabric, preventing sun light from reaching the fabric. On the other side it should not be too thick neither so that the mulch may dry out during sunny days. This will slow down the decomposition of mulch.

N.B. Plantex® Pro acts as a soil separator preventing the covering from mixing in with the soil. This means that less covering is needed with Plantex® than with just a mulch. Plantex® Pro is strong, very light and versatile, but an insufficient mulch covering may lead to very aggressive weeds growing through.

Plantex® Pro will last up to 25 years when covered. Our warranty* is not valid if passage of or contact with machines and/or equipment has taken place, for which our products are not suitable and which have resulted in a possible degradation of our products.

*For further information, please refer to our warranty terms and conditions.

